

6 in. (15 cm) Ceiling Speaker

Item: LPT-A104

- Excellent sound quality.
- Easily mounted.
- Comes with installation hardware.

Requires:
Speaker wire
R12, R14, R22 or R24 Room Modules

Specifications *	
Frequency Range	60 Hz - 20 kHz, -10 dB, Half Space
Power Capacity	30 W Continuous Program Power, 80 W Continuous Pink Noise
Nominal Sensitivity	90 dB SPL, 1 W @ 1 m
Nominal Coverage Angle	110° (Conical Coverage)
Nominal Impedance	8 ohms
Termination	Removable locking connector w/ screw-down terminals, 2 input terminals
Woofer	6.5" Polypropylene w/ Rubber
Tweeter	1/2" Mylar Tweeter
Cut out size	208 mm (8.18 in)
Net Weight	1.48 kg (3.26 lbs.)



* Specifications are subject to change without notice.

6 in. (15 cm) Plenum Rated Ceiling Speaker

Item: LPT-A104-P

- Plenum rated to meet fire code.
- Excellent sound quality.
- Easily mounted.
- Comes with installation hardware.

Requires:
Speaker wire
R12, R14, R22 or R24 Room Modules

Specifications *	
Frequency Range	60 Hz - 20 kHz
Nominal Sensitivity	89 dB SPL, 1 W @ 1 m (3.3 ft.)
Rated Maximum SPL	107 dB, 1 W @ 1 m (3.3 ft.)
Nominal Impedance	8 ohms
Power Handling	10 - 80 W
Termination	Removable locking connector w/ screw-down terminals, 2 input terminals
Woofer	6.5" Polypropylene w/ Rubber
Tweeter	1/2" Mylar Tweeter
Cut out size	208 mm (8.18 in)
Net Weight	1.48 kg (3.26 lbs.)



* Specifications are subject to change without notice.

8 in. (20 cm) Ceiling Speaker

Item: LPT-A105

- Larger diameter provides a greater range of sound than the 6 in. ceiling speaker.
- Excellent sound quality.
- Easily mounted.
- Comes with installation hardware.

Requires:
Speaker wire
R12, R14, R22 or R24 Room Modules

Specifications *	
Frequency Range	50 Hz - 20 kHz, -10 dB, Half Space
Power Capacity	40 W Continuous Program Power, 100 W Continuous Pink Noise
Nominal Sensitivity	91 dB SPL, 1 W @ 1 m
Nominal Coverage Angle	110° (Conical Coverage)
Nominal Impedance	8 ohms
Termination	Removable locking connector w/ screw-down terminals, 2 input terminals
Woofer	8" Polypropylene w/ Rubber
Tweeter	1/2" Mylar Tweeter
Cut out size	251 mm (9.88 in)
Net Weight	2.27 kg (5 lbs.)



* Specifications are subject to change without notice.

5 in. (13 cm) Wall Mount Speaker

Item: LPT-A106

- Use for rooms where speaker cannot be mounted into the ceiling grid structure.
- Excellent sound quality.
- Easily mounted.
- Comes with installation hardware.

Requires:
Speaker wire
R12, R14, R22 or R24 Room Modules

Specifications *	
Frequency Range	60 Hz - 18 kHz
Nominal Sensitivity	90 dB SPL, 1 W @ 1 m
Power Capacity	15 W
Nominal Impedance	8 ohms
Dimensions (W x D x H)	8.27 x 7.48 x 11.25 in. (21.00 x 18.99 x 28.57 cm)
Net Weight	2.79 kg (6.17 lbs.)



* Specifications are subject to change without notice.