

# SURGEX®

## THE WORLD LEADER IN POWER CONDITIONING TECHNOLOGIES



# SX1115RL

## SURGE ELIMINATOR & POWER CONDITIONER

- Advanced *Series Mode*® Surge Protection
- *SurgeX ICE*® Inrush Current Elimination
- *Impedance Tolerant*® EMI/RFI Filtering
- *COUVS*® Catastrophic Over/Under-Voltage Shutdown

The **SurgeX SX1115RL** is designed for **broadcast/recording studios, custom design/build installations and sound reinforcement applications.** It has front-panel connectors and a dimmer control for 2 Littlite® gooseneck lamps.

The SX1115RL provides guaranteed surge protection and power conditioning for audio, video, broadcast and computer equipment. The units are 15-amp load-capable and have 8 industrial grade grounded AC receptacles (6 switched, 2 always on).

The unit features both common mode and normal mode *Impedance Tolerant* EMI/RFI filtering, *SurgeX ICE* -Inrush Current Elimination and *COUVS* -Catastrophic Over/Under Voltage Shutdown for a complete power conditioning solution.

SurgeX Advanced *Series Mode* technology is superior to conventional MOV circuitry or MOV-Hybrid designs and is completely non-sacrificial. Our zero let-through technology provides the most reliable protection available. It stops all surges up to 6,000 volts (unlimited surge current) without producing harmful side effects such as ground contamination or common-mode disturbances.



**COUVS**  
**SURGEX ICE**  
Inrush Current Elimination

# SURGEX®

Professional AC Power Products  
[www.surgex.com](http://www.surgex.com)

10-YEAR WARRANTY

# SX1115RL

## SURGE ELIMINATOR & POWER CONDITIONER

- **Advanced Series Mode® Surge Protection**
- **Impedance Tolerant® EMI/RFI Filtering**
- **SurgeX ICE® Inrush Current Elimination**
- **COUVS® Catastrophic Over/Under-Voltage Shutdown**

### SPECIFICATIONS

**Load Rating:** 15 amps @ 120 volts.

**Power Requirement (no load):** 15 watts.

**Surge Let-Through Voltage (6000-volt surge):**  
0 volts.

**UL 1449 Adjunct Classification Test Results:** 1000 surges, 6000 volts, 3000 amps, B3 pulse; Measured suppressed voltage: 170 volts; no failures.

**Federal Guidelines:** Grade A, Class 1, Mode 1 (CID A-A-55818).

**EMI/RFI Filter, Normal Mode (50-ohm load):** 40 dB @ 100 kHz; 50 dB @ 300 kHz; 50 dB @ 3 MHz; 50 dB @ 30 MHz

**EMI/RFI Filter, Common Mode (50-ohm load):** 18 dB @ 300 kHz; 30 dB @ 1 MHz; 50 dB @ 5 MHz; 50 dB @ 20 MHz

**Maximum Applied Surge Voltage:** 6000 volts.\*

**Maximum Applied Surge Current:** Unlimited, due to current limiting.\*

**Maximum Applied Surge Energy:** Unlimited, due to current limiting.\*

**Endurance (C62.41-1991 Category B3 pulses):** 1 kV>500,000; 3 kV>10,000; 6 kV>1000.

**Undervoltage Shutdown:** 90 volts (resume at 100 v)

**Overvoltage Shutdown:** 145 volts (resume at 135 v)

**Maximum Load Inrush Current During Power-up:** 1000 Joules

**Littlite\*\* Connectors (QTY 2):** 12 volts AC, 500 mA each

**Dimensions:** 1.75" H x 19" W x 10.5" D  
(4.5 x 48.3 x 26.7 cm)

**Weight:** 11 lbs (5.0 kg)

**Temperature Range:** 5° to 35° C

**Humidity Range:** 5% to 95% R.H., non-condensing.

**Agency Listings:** ETL and cETL (UL 1449, 2nd edition; CSA C22.2 No.8-M1986, R2000)

\*1.2 x 50 µs pulse, industry standard combination wave surge, as per IEEE C62.41.

\*\* Littlite is a registered trademark of CAE, Inc.

### TECHNICAL DESCRIPTION

The SX1115RL shall be a one-rack-space unit in a magnetic shielding steel enclosure. It shall operate from 120 volts AC and have a 9-foot, grounded, 3-wire #14 line cord. There shall be 8 grounded AC receptacles on the back panel, with 6 switched and 2 always on. There shall be connectors and a dimmer for 2 Littlite gooseneck lamps on the front panel. Overall dimensions shall be 1.75" H x 19" W x 10.5" D. Weight shall be 11 pounds.

The SX1115RL shall have a load rating of 15 amps at 120 volts, a self-test circuit with visual indicator, and provide EMI/RFI filtering, inrush current elimination and catastrophic over/under-voltage shutdown. It shall meet Federal Grade A, Class 1, Mode 1 guidelines for powerline surge suppressors and withstand at least 1000 occurrences of surge pulse voltages up to 6000 volts.

### FEATURES

- Magnetic shielding steel enclosure
- 9' grounded 3-wire #14 line cord
- 8 grounded AC receptacles on rear panel (6 switched, 2 always on)
- Front-panel connectors and dimmer for Littlite lamps
- Advanced *Series Mode* surge protection
- Advanced *Impedance Tolerant* EMI/RFI filtering
- *SurgeX ICE* inrush current elimination technology
- *COUVS* catastrophic over/under-voltage shutdown
- Thermal circuit breaker overload protection
- Self-test circuit with visual indicator
- 10-year warranty
- **Made in U.S.A.**

**NO  
MOV'S**



**SURGEX®**

Professional AC Power Products

6131 Kellers Church Road • Pipersville, PA 18947

PH 215-766-1240 • FAX 215-766-9202

[www.surgex.com](http://www.surgex.com)

Specifications subject to change without notice. *SurgeX* is a division of New Frontier Electronics Inc.

This product, including its components and/or processes carried out thereby, are covered by one or more of the following:  
U.S. Pat. No. 4,870,534, 4,870,528, 6,728,089, 6,744,613, 7,068,487. Can. Pat. No. 1,333,191, 1,332,439. Other Patents Pending.